



Tour Performance Handlebar Riser for Energica Experia

Installation Instructions

1 1/2" Taller With Handlebar Set at 45 Degree Angle

**IMPROPER INSTALLATION COULD RESULT IN SERIOUS INJURY OR DEATH.
HAVE A QUALIFIED MECHANIC INSTALL YOUR HELIBARS.**

- 1.) Place a large shop rag over the body behind the handlebars. Using a 6mm hex loosen and remove all four pinch bolts and top clamp. Hold handlebar assembly as it will want to rotate down. **(See Photo #1)** Place bars in front of the triple clamp and rest them on rags to keep from scratching the components.
- 2.) Place the adapter in position as shown in **(Photo #3)** and install the M8 x 20mm screws provided. Torque the two forward screws (closest to fairing) first to **16 ft. lbs.** followed by the rear two screws (closest to rider). Make sure no rags have been pinched between the adapter and triple clamp.
- 3.) Place the handlebar assembly over the triple clamp bar mount and adjust bars left or right to center them **(See Photo #3)**.
- 4.) Put clamp cover into position and install the four OEM screws. Tighten the two forward screws first, enough to keep the bars from moving in the mount. Lightly tighten the two rear screws. **(See Photo #4)** Rotate bars forward or back to desired position. Starting with the forward two screws torque them to **16 ft. lbs.** **(See Photo #4)** Torque the rear two screws to **16 ft. lbs.**

**!! CAUTION!! BARS MUST BE TORQUED TO
SPECIFIED VALUES.
THEY MUST NOT BE OVER TORQUED.
OVERTIGHTENED HARDWARE CAN LOSE INTEGRITY.**

For questions regarding installation please call 978-895-1195

**HELI MODIFIED, INC ASSUMES NO LIABILITY FOR ANY INJURY OR LOSS OF PROPERTY
WHICH MAY RESULT FROM IMPROPER INSTALLATION OR USE OF ANY HELIBARS.**






Photo # 2




Photo # 4




Photo # 1




Photo # 3



Installation Instructions - HR16182
Energica of New England ~ 45 Fredette Street ~ Gardner, MA 01440
Phone: 978-895-1195